

H02216

MANGUERA PARA HIDROCARBUROS HYDROCARBON HOSE

SUCCIÓN Y DESCARGA DE COMBUSTIBLE TANK TRUCK Suction and Discharge of petroleum fuel

CONSTRUCCIÓN

Tubo Interno: Negro, liso, caucho NBR antiestático.

Refuerzo: Cordón sintético de alta resistencia y alambre helicoidal.

Cubierta: Negro, CR (acabado envuelto), caucho sintético, resistente al aceite, al combustible y a la intemperie.

Aplicación: Manguera rígida diseñada para la succión y el suministro de una amplia gama de combustibles derivados del petróleo con un contenido aromático de hasta el 50 % para camiones cisterna.

Rango de Temperatura: -29°C to + 71°C

CONSTRUCTION

Inner Tube: Black, smooth, Anti-static NBR rubber.

Reinforcement: High strength synthetic cord and helix wire.

Cover: Black, CR(wrapped finish), synthetic rubber, oil, fuel, and weathering resistant.

Application: Hardwall hose designed for suction and delivery of a wide range of petroleum fuel with aromatic content up to 50 % for Tank Trucks.

Temperature Range: -29°C to + 71°C

Aplicación / Application



Derivados del petróleo
Petroleum derivatives

Sector / Sector



Transporte
Transport



Agrícola
Agricultural



Industrial
Industrial



Marítimo
Maritime

Código Code	Diámetro Interno Hose I.D		Diámetro Externo Hose O.D		Presión Max. Trab. Working Pressure		Presión Min. Ruptura Burst Pressure		Succión Vacuum Rating		Radio de Curvatura Bending Radius		Rollo Roll	
	in	mm	mm	in	bar	psi	bar	psi	bar	InHg	mm	in	mts	fts
H02216-750	3/4"	19.1	29.0	1.14	10	150	30	450	0.9	27	75	3.00	60	196.85
H02216-1000	1"	25.4	35.0	1.38	10	150	30	450	0.9	27	100	3.94	60	196.85
H02216-1250	1.1/4"	31.5	42.0	1.65	10	150	30	450	0.9	27	125	4.92	60	196.85
H02216-1500	1.1/2"	38.0	49.8	1.96	10	150	30	450	0.9	27	150	6.10	60	196.85
H02216-2000	2"	50.8	63.8	2.51	10	150	30	450	0.9	27	205	8.07	60	196.85
H02216-2500	2.1/2"	63.5	76.9	3.03	10	150	30	450	0.9	27	255	10.0	60	196.85
H02216-3000	3"	76.2	90.2	3.54	10	150	30	450	0.9	27	305	12.0	60	196.85
H02216-4000	4"	101.6	117.5	4.65	10	150	30	450	0.9	27	405	16.0	60	196.85
H02216-6000	6"	152.4	170.0	6.69	10	150	30	450	0.9	27	685	27.0	30	98.43
H02216-8000	8"	203.2	224.0	8.82	10	150	30	450	0.9	27	1015	40.0	10	32.81

Refuerzo de cordón sintético de alta resistencia
High-strength synthetic cord reinforcement

Alambre helicoidal de acero
Spiral steel wire

Cubierta de caucho sintético Negro, CR (acabado envuelto)
Synthetic rubber cover
Black, CR (wrapped finish)



Tubo de caucho NBR antiestático negro, liso.
Anti-static NBR rubber tube
black, smooth.